



DURAGRIP[®]

Heavy duty vinyl flooring with easy clean,
Topguard™ PUR coated surface.


For areas where safety, hygiene and durability are paramount.



5706 Glacier



5753 Cottonseed



5756 Meadow




5710 Steelwork




5741 Wheat



5754 Moonlight



5733 Storm Burst



5758 Linen




5784 Cornflower



5749 Pitch Black



5761 Burnt Almond



5787 Tornado



DURAFLOOR

DURAGRIP

Heavy duty vinyl flooring with easy clean, Topguard™ PUR coated surface.

Performance

- **Hygiene** – more hygienic environment due to Duragrip's antibacterial and fungistatic treatment.
- **Longer Life** – Duragrip is produced from 100% PVC (no fillers) for superior performance and durability.
- **Easy to Maintain** – due to a non-porus surface of pure vinyl to ensure easier cleaning.
- **Colours** – increased colour clarity for complementing modern interiors.

Developed to meet the most demanding hygiene requirements. Duragrip is widely used in hospitals, care homes, schools, food processing areas and other flooring applications where safety, hygiene and durability are paramount. The high vinyl content makes Duragrip flexible and easier to instal as well as being very hard wearing which ensures it will perform with heavy foot traffic in most contact locations. With its attractive colour palette, Duragrip is also very popular for social housing use. For a copy of our installation guide, please contact our sales office.

Environment

- 100% Recyclable
- Contains Recycled Content
- No waxes / polishes for life

Duragrips longevity and green credentials ensure that it will give an excellent performance as well as reducing the impact on the environment.

Maintenance

No waxes or polishes are required. For a copy of our Maintenance Guide please contact our sales office.

Guarantee

Duragrip is offered with a 12 year commercial wear guarantee - for full guarantee details please contact our sales office.



Product Specifications

Dimensions



Total Thickness
2.0mm



Total Weight
2,700gm²



Width of Roll
2m



Length of Rolls
20m

Technical Data



Wear Rating
EN 685/34/43



EN685/34

EN685/43



Fire Rating
EN 13501-1 / Bfl - s1
ASTM E 648/662 / class1 / pass



Slip Resistance
RRL Pendulum Test (wet) - > 36
DIN 51130 - R10



Light Fastness
EN ISO 105-B02 - Grade 6



Dimensional Stability
EN ISO 23999
Max - 0.2%



Residual Indentation
EN ISO 24343
0.1mm



Chemical Resistance
EN ISO 26987 / ASTM F925-02
Good Resistance

Attributes



Flexible



Easy to clean



Tough & durable

DURAFLOOR

01592 630 030

uksales@duraflor.com

DURAFLOOR.COM