
RESOLUTE


Heavy duty vinyl flooring with easy clean, Topguard™ PUR coated surface.

For areas where safety, hygiene and durability are paramount.





5826 Flint




5842 Manatee



5814 Slate




5825 Vulcan




5835 Pearl



5822 Argent



5810 Aero



5808 Flax



RESOLUTE

Heavy duty vinyl flooring with easy clean, Topguard™ PUR coated surface.



Performance

- Safer safer environment due to Resolute's anti-slip surface.
- Longer Life With a very heavy commercial and heavy industrial rating, Resolute will give excellent lifecycle cost.
- Easy to Maintain the fleck design and the Topguard™ PUR coated surface ensures efficiency and ease of cleaning.
- Superior Design available in a popular range of designs, Resolute is a versatile product that has an application in many types of interiors.

Developed to meet the needs of specifiers and end users alike, Resolute is ideal for commercial buildings including schools and institutions, nursing homes, hospitals, offices and retail outlets as well as giving excellent durability for domestic / social housing use. Its popular colour range and Topguard™ PUR coated surface make it very suitable for modern, distinctive interiors that need a performance floorcovering. For a copy of our installation guide, please contact our sales office.

Environment

- 100% Recyclable
- Contains Recycled Content
- No waxes / polishes for life

Resolute's longevity and green credentials ensure that it will give an excellent performance as well as reducing the impact on the environment.

Maintenance

Designed for heavy wear areas, Resolute is easy to maintain. For a copy of our Maintenance Guide please contact our sales office.

Guarantee

Resolute is offered with a 12 year commercial wear guarantee - for full guarantee details please contact our sales office.

Product Specifications Dimensions Total Thickness Total Weight 2,700gm² Width of Roll **Length of Rolls Technical Data Wear Rating** EN 685/34/43 **Fire Rating** EN 13501-1 / Bfl - s1 ASTM E 648/662 / class1 / pass Slip Resistance RRL Pendulum Test (wet) - > 36 DIN 51130 - R10 **Light Fastness** EN ISO 105-B02 - Grade 6 Residual **Dimensional Stability Indentation** EN ISO 23999 EN ISO 24343 **Chemical Resistance** EN ISO 26987 / ASTM F925-02 **Good Resistance Attributes** Flexible Easy to clean

DURAFLOR

01592 630 030 uksales@duraflor.com

DURAFLOR.COM

