DURAFLOR

SAFETY FLOORING

Cleaning & Maintenance

Grab slip resistant floorings provide increased protection against slipping due to their special structure surface and chemical composition. For these flooring types we recommend only machine cleaning techniques. Wax and polish should not be used on safety vinyl floors.



Initial Cleaning After Installation

- 1. Remove all dirt and dust with vacuum from the surface and use a mono-disc machine with a red pad. Use strong alkaline detergent (pH11-13)
- 2. Scrub the floor to clean.
- 3. The soiled water should be removed with a wet vacuum cleaner.
- 4. Rinse the floor with clean water at least twice, mop up the water and allow the surface to dry.
- 5. If the room is small and cannot be machine cleaned, use a scrubbing brush.

Routine & Periodic Maintenance

- 1. Remove all dirt and dust with a vacuum from the surface and use mono-disc machine with white or red pad, using soft alkaline detergent (pH8-10) or neutral detergent.
- 2. Scrub the floor to clean.
- 3. The soiled water should be removed with a wet vacuum cleaner, then rinse the floor with clean water at least twice, mop up the water and allow the surface to dry.
- 4. If the room is small and cannot be machine cleaned, use a scrubbing brush.

Protection

No amount of maintenance will keep a floor looking good if measures are not taken to reduce the amount of dirt that is trafficked onto the floor. Duraflor recommend suitable barrier mattings are used and that these mattings are maintained correctly.

Rubber can permanently stain PVC floorcoverings. Avoid using rubber backed mats, rubber furniture feet or rubber wheeled castors.

LONDON

47 Gee Street Clerkenwell London EC1V 3RS

01592 630 030 london@duraflor.com

LEEDS

Vitality House Milford Place Leeds LS4 2BQ

0113 243 2131 leeds@duraflor.com

SCOTLAND

Unit 14 Faraday Road Glenrothes KY6 2RU

01592 630 030 uksales@duraflor.com

DURAFLOR.COM

DURAFLOR

Stain Removal

Ink, Tomato, Mustard, Blood, Urine,	Diluted bleach (let it act without
Excrement	rubbing then rinse thoroughly)
Rust	Anti-rust or oxalic acid (rinse thoroughly)
Heavy grease, Paint, Rubber traces,	White Spirit
Hair colour, Ball Point or Felt Pens	

For further advice, please contact our technical department, who will be happy to advise on the correct methods to use and can help you put together an effective cleaning programme.

LONDON

47 Gee Street Clerkenwell London EC1V 3RS

01592 630 030 london@duraflor.com LEEDS

Vitality House Milford Place Leeds LS4 2BQ

0113 243 2131 leeds@duraflor.com SCOTLAND

Unit 14 Faraday Road Glenrothes KY6 2RU

01592 630 030 uksales@duraflor.com